

H.A.R.D. 115 SP

FEATURES

- Very low-profile (39 cm), high output (138dB SPL/1 m, full-range) self-powered monitor with 15" woofers (LF) Neodymium magnet and a (HF) compression driver with reflective folded wave guide loaded, 2.56" titanium diaphragm.
- Built-in PWM digital amplifier + DSP with high performance (1,000 W/8 Ω)
- Patented both on construction design and on the reflective folded wave guide
- Very light weight (25 kg) to facilitate handling
- Very low feedback reaction
- Extremely linear frequency response and phase response of just $\pm 45^\circ$ from 500Hz to 16kHz
- Asymmetric design with dual floor or flying installation angle
- Balanced sound emission with listening distance varying between 0 and 3 metres
- Cabinet reinforced internally for maximum sturdiness and resonance elimination and fitted with 8 multi-purpose mounting points, which can be used to fit either flying rings or wheels.



APPLICATIONS

- Medium-power live applications
- No-nonsense use with live bands
- TV studios and theatres, thanks to the "ultra-low" profile compatible with camera sightlines and set requirements
- Near-field stage monitor.

DESCRIPTION

H.A.R.D. 115 SP is a wide-range, two-way self-powered loudspeaker system with passive crossover, has a built-in high-powered amplifier, delivering 1.000W/8Ω optimised for floor stage monitoring, made by low frequency section using four a NdFeB 15" woofer in "reflex" configuration and a high frequency section using a NdFeB compression driver, 1.41" throat and 2.56" titanium diaphragm, loaded by a folded wave guide (S.P.R.W.G.) which applies the principles of diffraction, reflection and absorption.

This wave guide is an integral part of the cabinet and enables the control, over the entire spectrum reproduced, of the acoustic emission in a clearly defined angle on the horizontal and vertical plane, with very compact dimensions compared to its acoustic performance. This patented innovation allows to obtain a useable bandwidth reproduced from 59Hz to 15kHz at -10 dB, with a linearity within ± 3 dB from 75Hz to 13.5kHz.

Placed on the floor and driven at max. peak power, the system is able to produce a max. peak of 138 dB SPL at 1 meter.

The enclosure has an asymmetric design with dual floor or flying installation angle. Built in high quality 15 mm baltic birch plywood, and the external dimensions are extremely compact, particularly the height from the floor (just 39 cm), considerably reducing the visual impact when the enclosure is positioned on stage ready for use. The black outer finish is in high quality scratch-resistant waterproof black paint.

The cabinet has 8 mounting points and two practical integral recessed handles on the cabinet ensuring a positive grip during handling. The front grille which protects the speakers is vibration-free painted steel mesh.

TECHNICAL SPECIFICATIONS:

FREQUENCY RESPONSE	(-10 dB) (± 3 dB)	59 Hz \div 15 kHz 75 Hz \div 13.5 kHz
AVERAGE DISPERSION	>5 kHz	27° x 71° (H x V)
IMPEDANCE (Ω)	Nominal	8
INPUT SENSITIVITY	1.12 V	(3.2 dBu)
BUILT-IN PWM AMP POWER (W RMS)		1000 @ 8 Ω (Full range, passive crossover)
MAX SPL @ 1 m (calculated)	Peak	138

CONNECTORS	Audio Mains	1 XLR + 1 Link Out 1 PowerCon + 1 Link Out
-------------------	----------------	---

LOUDSPEAKERS AND LOADING	Low High	1 x 15" NdFeB, Hi pass vented box 1 x 1.4" Exit (2.56" diaphragm) NdFeB
---------------------------------	-------------	--

WEIGHT	<i>Single unit</i> 25 kg (55.1 lb)	<i>Shipping (1 unit)</i> 30 kg (66.1 lb)
---------------	---------------------------------------	---

DIMENSIONS	39 cm (15.4")	47 cm (18.5")
Height	45 cm (17.7")	52 cm (20.5")
Width	60 cm (23.6")	64 cm (25.2")
Depth		